



Supplying North America with fine hardwood flooring for over 10 years

## **Elegance 6” wire brushed specifications:**

- Grade: ABC. Mostly select material showing the occasional sound knot and mineral
- Width: 6” - Thickness: 9/16” – Wear layer: 3mm sawn veneer. Fixed lengths: 6’ (72”)
- 3 ply hardwood core. Micro beveled edges and ends
- 7 coats of urethane with one coat of aluminum oxide. Anti scratch, low gloss finish
- Brushed finish showing grain texture, smooth sanded, no hand scraping.
- Carton size: 23.7 square feet. 40 lbs per carton
- 25 year residential warranty. 3 year limited commercial warranty
- Approved for below, on or above grade installation
  - Nail using 18 gauge staples. Maximum 8” apart
  - Direct glue down using recommended Bostik adhesive
  - Float over 3mm high-density foam underlay
  - For floating use PVA adhesive
- This radiant heat approved flooring product should be acclimated into dry, normal living conditions for 7 days while the radiant heat system is on. A thermostat dial must be installed and the heat left on at 20c. The heat should not exceed 24c or dip below 16c. Adjust the heat slowly at a rate not exceeding 5 degrees celsius per day. This will avoid shocking the wood. A relative humidity of between 35% and 55% should be maintained before, during and after installation.
- Note: all wood flooring products shrink and expand. Proper site preparation, climate control and heat system operation are key to avoiding excessive movement in any wood floor product.
- Site preparation:
  - Confirm plywood subfloor is dry to 12% moisture before proceeding.
  - Concrete subfloors should be confirmed dry at 3 lbs of MVER’s per 1000sqft
  - Level the subfloor to 1/8” + or – over 10’
  - Install a 6mm polyethylene vapor barrier beneath the foam underlay for floating installations. This should be overlapped 6” at every join and sealed with tape
  - Crawl spaces should be heated and vented
  - All wet trades such as drywall and tile work should be complete.
  - Only acclimate flooring into dry site conditions and temperatures between 16c and 24c. Relative humidity should be between 35 to 55%. It is the responsibility of the homeowner to maintain these conditions year round. Failure to do so can result in splits, cupping, buckling and squeaking. These conditions are not covered under warranty.
  - Open 3 or 4 packs of flooring to blend the grading and colour difference. It is the responsibility of the installer to sort material in accordance with the grade purchased.
  - Transitions are recommended at doorways. Avoid long unbroken runs of 30’ +.
  - Allow ¼” expansion gaps at all perimeters and transitions to other flooring
- Return unopened packs within 30 days for full refund. After 30 days 25% restocking fee.